

BERN et al.  
Appl. No. 09/897,896  
September 16, 2005

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A communication network for transporting calls, comprising:

a plurality of switching nodes, each switching node containing routing means (for routing calls through said communication network;

service provision means for providing predetermined services in said communication network, where at least a part of said service provision means is provided in at least one of said plurality of switching nodes, said service provision means being arranged to provide at least one service according to which said service provision means are able to set up calls in said at least one switching node in response to the request of a user of said at least one service virtual subscriber requesting that a call be set up in accordance with a virtual subscription, and said service provision means being arranged to add user virtual subscriber identification information to the call data of a call set up by said service provision means, ~~said user identification information identifying said user of said service requesting that a call be set up for allowing interception of said call.~~

2. (Previously Presented) A communication network according to claim 1, further comprising call interception means for performing a call interception operation on a call in said communication network in response to detecting predetermined interception trigger information in the call data of a call.

3. (Previously Presented) A communication network according to claim 2, wherein

BERN et al.  
Appl. No. 09/897,896  
September 16, 2005

said call interception means is arranged to be able to detect said user identification information as said interception trigger information.

4. (Previously Presented) A communication network according to claim 2, wherein a respective call interception means is provided in association with each routing means in each of said plurality of switching nodes.

5. (Previously Presented) A communication network of claim 4, wherein said call interception means is provided as part of said routing means.

6. (Previously Presented) A communication network according to claim 2, wherein said call interception means contains a memory means for storing said interception triggering information, and is arranged to communicate with an interception management means, such that said interception management means provides said call interception means with the interception trigger information and controls the content of said memory means.

7. (Previously Presented) A communication network according to claim 6, wherein said call interception means is arranged such that said call interception operation comprises sending data from an intercepted call to said interception management means.

8. (Previously Presented) A communication network according to claim 2, wherein said call interception means is arranged such that said call interception operation comprises establishing a three-way conference call for an intercepted call, where one of the destinations is the origin of the call, one is the one or more physical destinations specified in the call, and one is a monitoring agency.

9. (Previously Presented) A communication network according to claim 1, wherein said service provision means comprise

BERN et al.  
Appl. No. 09/897,896  
September 16, 2005

- a service switching means provided in a switching node of said network for detecting service triggering information in a call,

- a service control means that is arranged to communicate with said service switching means, such that said service switching means notifies said service control means upon detecting service triggering information in a call and said service control means instructs said service switching means how to proceed with said call containing said service triggering information and provides said service switching means with said user identification information.

10. (Previously Presented) A communication network according to claim 9, further comprising

- a service data means for storing data on provided services and data on users subscribing to specific services, and

- a service management means for managing which services are provided and for controlling the writing of data into said service data means.

11. (Previously Presented) A communication network according to claim 1, wherein said service provision means are furthermore arranged to add service identification information to the call data of a call being set up by said service provision means, said service identification information identifying the service that said user requesting that a call be set up has invoked.

12. (Previously Presented) A communication network according to claim 1,

wherein said service provision means comprise a service data means, in which user data associated with users of provided services and service data associated with provided services are stored, said service provision means being arranged such that a user has access to at least a part of the user data associated with him and may change said user data to which he has access.

BERN et al.  
Appl. No. 09/897,896  
September 16, 2005

13. (Previously Presented) A communication network according to claim 12, wherein said service provision means further comprise a service switching means provided in a switching node of said network for detecting service triggering information in a call, and a service control means that is arranged to communicate with said service switching means and said service data means, where said service switching means notifies said service control means upon detecting service triggering information in a call and said service control means instructs said service switching means how to proceed with said call containing said service triggering information and provides said service switching means with said user identification information, and where said user has access to said at least part of his user data via said communication network and said service switching means.

14. (Previously Presented) A communication network according to claim 12, wherein said service provision means is arranged to communicate with a computer network, and where said user has access to said at least part of his user data via said computer network.

15. (Original) A communication network according to claim 14, wherein said computer network is the Internet.

16. (Previously Presented) A communication network according to claim 12, wherein said service provision means are arranged to provide a monitoring agency continuous access to user data of selected users.

17. (Previously Presented) A communication network according to claim 12, wherein said service provision means are arranged to perform a user data change interception operation in response to a user changing his user data.

BERN et al.  
Appl. No. 09/897,896  
September 16, 2005

18. (Previously Presented) A communication network according to claim 1,  
said communication network comprising call interception means for performing a call  
interception operation on a call in said communication network in response to detecting  
predetermined interception trigger information in the call data of said call, said call interception  
means being arranged to be able to detect said user identification information as said interception  
trigger information and having a memory means for storing said interception trigger information,  
said service provision means comprising a service data means, in which user data  
associated with users of provided services and service data associated with provided services are  
stored, said service provision means being arranged such that a user has access to at least a part  
of the user data associated with him and may change said user data associated with him to which  
he has access, and said service provision means being arranged to perform a user data change  
interception operation in response to a user changing his user data,  
where said user data change interception operation comprises sending user identification  
information associated with the user who changed his user data to the call interception means,  
and said call interception means being arranged to compare said user identification information  
with interception trigger information stored in said memory means and sending a user data  
change message to a monitoring agency if said user identification information matches with a  
piece of interception trigger information stored in said memory means.

19. (Original) A communication network according to claim 18,  
wherein said user data change message contains information on the user who changed his  
user data and information at least on the changes performed.

BERN et al.  
Appl. No. 09/897,896  
September 16, 2005

20. (Previously Presented) A communication network according to claim 1, said communication network comprising call interception means for performing a call interception operation on a call in said communication network in response to detecting predetermined interception trigger information in the call data of said call, said call interception means being arranged to be able to detect said user identification information as said interception trigger information and having a memory means for storing said interception trigger information, and is arranged to communicate with an interception management means, such that said interception management means provides said call interception means with the interception trigger information and controls the content of said memory means,

said service provision means comprising a service data means, in which user data associated with users of provided services and service data associated with provided services are stored, said service provision means being arranged such that a user has access to at least a part of the user data associated with him and may change said user data associated with him to which he has access, and said service provision means being arranged to perform a user data change interception operation in response to a user changing his user data,

where said user data change interception operation comprises sending user identification information associated with the user who changed his user data to the interception management means, and said interception management means being arranged to compare said user identification information with interception trigger information stored in said interception management means and sending a user data change message to a monitoring agency if said user identification information matches with a piece of interception trigger information stored in said interception management means.

BERN et al.  
Appl. No. 09/897,896  
September 16, 2005

21. (Original) A communication network according to claim 20,  
wherein said user data change message contains information on the user who changed his  
user data and information at least on the changes performed.
22. (Original) A communication network according to claim 1,  
wherein the format of the call data for a call being transported through said  
communication network is specified by a predetermined call data protocol and said call data  
protocol specifies fields for predetermined types of call data and fields which are not used by  
said call data protocol.
23. (Previously Presented) A communication network according to claim 22,  
wherein said service provision means adds said user identification information to said call  
data by manipulating data in a field specified for predetermined types of call data.
24. (Original) A communication network according to claim 23,  
wherein said call data protocol specifies a format and field for user identification  
information.
25. (Previously Presented) A communication network according to claim 22,  
wherein said service provision means adds said user identification information to said call  
data by manipulating data in a field not used by said call data protocol.
26. (Currently Amended) A method of arranging a service provision means providing  
predetermined services in a communications network for transporting calls, said communication  
network having a plurality of switching nodes, each switching node containing routing means for  
routing calls through said communication network, said method comprising:  
providing at least a part of said service provision means in at least one of said plurality of  
switching nodes,

BERN et al.  
Appl. No. 09/897,896  
September 16, 2005

arranging said service provision means to provide at least one service according to which said service provision means are able to set up calls in said at least one switching node in response to the request of a virtual subscriber requesting that a call be set up in accordance with a virtual subscription, user of said at least one service, and

arranging said service provision means to add ~~user~~ virtual subscriber identification information to the call data of a call set up by said service provision means, ~~said user~~ identification information identifying said user of said service requesting that a call be set up for allowing interception of said call.

27. (Previously Presented) A communication network for transporting calls, comprising:

a plurality of switching nodes, each switching node containing routing means for routing calls through said communication network;

service provision means for providing predetermined services in said communication network, said service provision means comprising a service data means (71) in which user data associated with users of provided services and service data associated with provided services are stored, said service provision means being arranged such that a user has access to at least a part of the user data associated with him and may change said user data to which he has access,

wherein said service provision means are arranged

to provide a monitoring agency continuous access to user data of selected users, or

to perform a user data change interception operation in response to a user changing his user data.



BERN et al.  
Appl. No. 09/897,896  
September 16, 2005

28. (Previously Presented) A communication network according to claim 27, wherein said service provision means further comprise a service switching means provided in a switching node of said network for detecting service triggering information in a call, and a service control means that is arranged to communicate with said service switching means and said service data means, where said service switching means notifies said service control means upon detecting service triggering information in a call and said service control means instructs said service switching means how to proceed with said call containing said service triggering information and provides said service switching means with said user identification information, and where said user has access to said at least part of his user data via said communication network and said service switching means.

29. (Previously Presented) A communication network according to claim 27, wherein said service provision means is arranged to communicate with a computer network, and where said user has access to said at least part of his user data via said computer network.

30. (Original) A communication network according to claim 29, wherein said computer network is the Internet.

31. (Previously Presented) A communication network according to claim 27, said communication network comprising call interception means for performing a call interception operation on a call in said communication network in response to detecting predetermined interception trigger information in the call data of said call, said call interception means being arranged to be able to detect user identification information that identifies users of services provided by said service provision means as said interception trigger information and having a memory means for storing said interception trigger information,

BERN et al.  
Appl. No. 09/897,896  
September 16, 2005

where said user data change interception operation comprises sending user identification information associated with the user who changed his user data to the call interception means, and said call interception means being arranged to compare said user identification information with interception trigger information stored in said memory means and sending a user data change message to a monitoring agency if said user identification information matches with a piece of interception trigger information stored in said memory means.

32. (Original) A communication network according to claim 31,

wherein said user data change message contains information on the user who changed his user data and information at least on the changes performed.

33. (Previously Presented) A communication network according to claim 27,

said communication network comprising call interception means for performing a call interception operation on a call in said communication network in response to detecting predetermined interception trigger information in the call data of said call, said call interception means being arranged to be able to detect identification information that identifies users of services provided by said service provision means as said interception trigger information, and having a memory means for storing said interception trigger information, and is arranged to communicate with an interception management means, such that said interception management means provides said call interception means with the interception trigger information and controls the content of said memory means,

where said user data change interception operation comprises sending user identification information associated with the user who changed his user data to the interception management means, and said interception management means being arranged to compare said user identification information with interception trigger information stored in said interception

BERN et al.  
Appl. No. 09/897,896  
September 16, 2005

management means and sending a user data change message to a monitoring agency if said user identification information matches with a piece of interception trigger information stored in said interception management means.

34. (Original) A communication network according to claim 33,

wherein said user data change message contains information on the user who changed his user data and information at least on the changes performed.

35. (Previously Presented) Apparatus for use in a communication network including a plurality of switching nodes for transporting calls and for providing predetermined services, each switching node including a router for routing calls through said communication network, the apparatus comprising:

electronic circuitry configured to assist in setting up a call in one of the switching nodes in response to a virtual subscriber requesting that a call be set up and to add virtual subscriber identification information to call data of the set up call.

36. (Previously Presented) The apparatus according to claim 35, further comprising call interception circuitry configured to perform a call interception operation in response to detecting said virtual subscriber identification information in the call data of a call.

37. (Previously Presented) The apparatus according to claim 36, wherein said call interception operation includes sending data from an intercepted call to an interception management entity.

38. (Previously Presented) The apparatus according to claim 37, wherein said call interception operation includes establishing a three-way conference call for an intercepted call, where one destination is an origin of the call, one destination is one or more physical destinations specified in the call, and one destination is a monitoring agency.

BERN et al.  
Appl. No. 09/897,896  
September 16, 2005

39. (Previously Presented) The apparatus in claim 35, wherein the virtual subscriber has a virtual subscription that is not associated with an access point to the communication network, and wherein the call is associated with the virtual subscription.

40. (Previously Presented) The apparatus in claim 39, wherein the virtual subscriber may access the communication network, via any access point, and an identification of that access point is not specifically associated with the virtual subscriber.

41. (Previously Presented) The apparatus in claim 39, wherein the virtual subscription is a dialable type of virtual subscription which permits only outgoing calls initiated by the virtual subscriber.

42. (Previously Presented) The apparatus in claim 39, wherein the virtual subscription is a non-dialable type of virtual subscription which permits only incoming calls addressed to the virtual subscriber.

43. (Previously Presented) The apparatus in claim 39, wherein when the virtual subscriber accesses the communication network at an access point, identification of that access point does not provide a trigger for an interception operation because that access point is not specifically associated with the virtual subscriber.

44. (Previously Presented) A method of providing predetermined services in a communication network for transporting calls, said communication network having a plurality of switching nodes, each switching node containing a router for routing calls through said communication network, said method comprising:

providing a communications service to set up a call in at least one switching node in response to a request of a virtual subscriber for service, and

adding virtual subscriber identification information to the call data of the set up call.

BERN et al.  
Appl. No. 09/897,896  
September 16, 2005

45. (Previously Presented) The method in claim 44, wherein the virtual subscriber has a virtual subscription that is not associated with an access point to the communication network, and wherein the call is associated with the virtual subscription.

46. (Previously Presented) The method in claim 45, wherein the virtual subscriber access the communication network via any access point, and an identification of that access point is not specifically associated with the virtual subscriber.

47. (Previously Presented) The method in claim 45, wherein the virtual subscription is a dialable type of virtual subscription which permits only outgoing calls initiated by the virtual subscriber.

48. (Previously Presented) The method in claim 45, wherein the virtual subscription is a non-dialable type of virtual subscription which permits only incoming calls addressed to the virtual subscriber.

49. (Previously Presented) The apparatus in claim 45, wherein when the virtual subscriber accesses the communication network at an access point, identification of that access point does not provide a trigger for an interception operation because that access point is not specifically associated with the virtual subscriber.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**